

UHF Ground Independent Mopole™

The CD50 and CD51 Series UHF ground independent Mopole™ antennas are versatile and popular antennas, providing excellent performance in virtually any mounting position.

When mounted on a vehicle gutter or similar position, these UHF Mopoles™ provide optimum performance with a largely omnidirectional pattern. Due to the low angle of radiation inherent in the dipole antenna pattern, a 4.0 dB improvement in performance is typical when compared to a ¼ wave whip in the centre of a metal roof.

The end fed design of the UHF Mopoles™ incorporates a truly unique transformer in the base section. In this patented feed assembly, the dielectric of the coaxial feeder cable is trimmed to a set length and then introduced into the coil in termination. The result is a precisely matched feed which is so consistent that tuning to frequency from a chart becomes a matter of course.

CD51 antennas are fitted with a flexible nylon radome over a copper element - ideal in industrial applications. CD50 antennas have an elegant and durable tapered stainless steel whip section.

There are two styles of mounting arrangements offered. The CD50-xx-70 and CD51-xx-70 versions mount via a threaded stud and nut assembly. The antenna can be easily terminated, tuned and re-terminated in the field using the instructions supplied. Its patented design allows the coaxial cable to be replaced in the field without specialised tools or soldering.

The CD50-xx-50 and CD51-xx-50 versions mate with the MBC coaxial base providing an internal, permanent connection in a completely sealed unit. The MBC base is easy to install and allows the entire antenna to be removed and replaced at will.

- Versatile - Ground plane independence allows alternative mounting locations
- Performance - High performance and largely omni-directional pattern when not centre roof mounted
- Convenient - Patented design allows termination or re-termination in seconds
- Stainless steel whip or flexible nylon whips cater to individual needs
- Durable - Base coil is virtually indestructible
- Unique transformer design
- Australian Patents #596830 and #656793





UHF Ground Independent Mopole™

380-520MHz

**CD50 Series
CD51 Series**


Typical VSWR response (CD51)



UHF Mopoles™ are excellent performers even when gutter mounted as this pattern demonstrates. The Mopole™ design has resulted in an antenna which is largely omnidirectional in spite of its gutter mounting position.

TEST FREQUENCY: 460 MHz
REFERENCE ANTENNA
MODEL: SW7
MOUNT: MB10 Roof Centre
TEST ANTENNA
MODEL: CD51
MOUNT: GM2 Gutter Drivers Side


MOUNTING NOTES



Although the CD51 Mopole™ style works extremely well when gutter mounted, moving the antenna down to the vehicle fender, as shown here, will result in severe pattern degradation. This antenna should not be used in this mounting position.

TEST FREQUENCY: 460MHz
REFERENCE ANTENNA
MODEL: SW7
MOUNT: MB10
POSITION: Roof Centre
TEST ANTENNA
MODEL: CD51
MOUNT: Trunk Mount
POSITION: Rear Driver Side

CD50-xx-70 cross section with cable fitted



Electrical

Model No.	CD50-65-50	CD50-65-70	CD50-68-50	CD50-68-70	CD51-65-50	CD51-65-70	CD51-68-50	CD51-68-70
Gain	4dB over a ¼ wave. See note (1)							
Frequency MHz	380 - 440		450 - 520		380 - 440		450 - 520	
Power W	50							
Tuned Bandwidth	13 MHz @ <1.5:1 VSWR							
Tuning	Field tune to minimum VSWR using supplied tuning chart							

Mechanical

Model No.	CD50-XX-50	CD50-XX-70	CD51-XX-50	CD51-XX-70
Whip Material	17-7 PH Stainless steel		Copper braid element in flexible nylon tubing	
Whip Length inches	15"		14"	
Mounting	MBC base (included)	Threaded stud	MBC base (included)	Threaded stud
Cable and Connector	Not included, order separately. See note (2)			

(1) Mopole™ antennas such as the CD50 and CD51 exhibit a 4dB improvement in performance over a ¼ wave whip but in pattern tests deliver only 2.0 to 2.5dB of actual gain. This improvement in performance can be attributed to a lower angle of radiation and is of particular benefit to users in rugged terrain conditions and in heavily built up city areas.

(2) Available preterminated with 16ft 8058 RG58C/U. Use -73 or -53 suffix to replace -70 or -50 suffix.

Australian Patent No. 596830 and 656793

P-40345-5

rfiantennas.com

